

U.S. Patent Application No. 09/995,888
Amendment dated May 3, 2004
Reply to Office Action dated February 2, 2004

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claim 1 (original): A filter cartridge assembly comprising:

a tubular housing having an inner wall, an outer wall, a first end, and a second end, said inner wall including at least a first section, a second section, and a third section, said first section having a first length in a direction from said first end to said second end and a first average inner diameter, said second section having a second length in a direction from said first end to said second end and a second average inner diameter that is smaller than said first average inner diameter, said third section having a third length in a direction from said first end to said second end and a third average inner diameter that is smaller than said second average inner diameter, wherein the inner wall of said tubular housing includes a first shoulder at the intersection of said first section and said second section and a second shoulder at the intersection of said second section and said third section; and

a plurality of filter media sections, including a first filter media section, within the tubular housing and radially contained by said inner wall, each of said plurality of filter media sections having a different filter media composition, wherein said first filter media section has a length in a direction from said first end to said second end that includes at least portions of at least two of said lengths of the inner wall sections such that said first media section traverses at least one of said shoulders.

Claim 2 (original): The assembly of claim 1, wherein said assembly further comprises:

a first connector that seals the first end of said tubular housing except at a centrally-located entrance port in said connector where fluid is capable of entering the assembly; and

U.S. Patent Application No. 09/995,888
Amendment dated May 3, 2004
Reply to Office Action dated February 2, 2004

a second connector that seals the second end of said tubular body except at a centrally-located exit port where fluid is capable of exiting the cartridge.

Claim 3 (original): The assembly of claim 2, wherein said assembly further contains a dialysate fluid.

Claim 4 (original): The assembly of claim 2, wherein said tubular housing comprises a plastic material.

Claim 5 (original): The assembly of claim 4, wherein said plastic material comprises a polypropylene material.

Claim 6 (original): The assembly of claim 1, wherein the thickness of said inner wall is less than, or equal to, about 0.125 inch.

Claim 7 (original): The assembly of claim 1, wherein said first filter media section traverses said first shoulder, said plurality of filter media sections includes a second filter media section, said second filter media section has a different filter media composition than said first filter media section, said second filter media section has a length in a direction from said first end to said second end that includes at least portions of said second length and said third length of said inner wall sections, and said second media section traverses said second shoulder.

Claim 8 (original): A system including the assembly of claim 2, in combination with a fluid circulating device, wherein said device has an outlet and an inlet, said entrance port is in fluid communication with said outlet, and said exit port is in fluid communication with said inlet.

Claim 9 (original): A method of filtering a fluid, comprising circulating said fluid through the system of claim 8.

Claim 10 (original): A method of preparing the assembly of claim 2, comprising:
providing said tubular housing;

U.S. Patent Application No. 09/995,888
Amendment dated May 3, 2004
Reply to Office Action dated February 2, 2004

sealing one of said first and second end connectors to said tubular housing;
introducing a first of said filter media sections into said tubular housing;
settling said first media section in said tubular housing; and
sealing the other of said first and second connectors to said tubular body.

Claim 11 (original): A filter cartridge housing comprising:

a tubular housing having a conical shape and including a straight inner wall, an outer wall, a first end, and a second end, said inner wall including at least a first section, a second section, and a third section, said first section having a first length in a direction from said first end to said second end and a first average inner diameter, said second section having a second length in a direction from said first end to said second end and a second average inner diameter that is smaller than said first average inner diameter, said third section having a third length in a direction from said first end to said second end and a third average inner diameter that is smaller than said second average inner diameter; and

a first annular flow director extending radially inwardly from the inner wall of said tubular housing at the intersection of said first section and said second section, and a second annular flow director extending radially inwardly from the inner wall at the intersection of said second section and said third section.

Claim 12 (currently amended): An assembly comprising:

the filter cartridge housing of claim ~~10~~ 11; and

a plurality of filter media sections, including a first filter media section, within the tubular housing and radially contained by said inner wall, each of said plurality of filter media sections having a different filter media composition, wherein said first filter media section has a length in a direction from said first end to said second end that includes at least portions of at least two of said

U.S. Patent Application No. 09/995,888
Amendment dated May 3, 2004
Reply to Office Action dated February 2, 2004

lengths of the inner wall sections such that said first media section traverses at least one of said first and second annular flow director.

Claim 13 (original): The assembly of claim 12, wherein said assembly further comprises:

a first connector that seals the first end of said tubular housing except at a centrally-located entrance port in said connector where fluid is capable of entering the assembly; and

a second connector that seals the second end of said tubular body except at a centrally-located exit port where fluid is capable of exiting the cartridge.

Claim 14 (original): The assembly of claim 13, wherein said assembly further contains a dialysate fluid.

Claim 15 (original): The filter cartridge housing of claim 11, wherein said tubular housing comprises a plastic material.

Claim 16 (original): The filter cartridge housing of claim 15, wherein said plastic material comprises a polypropylene material.

Claim 17 (currently amended): The filter cartridge housing of claim ~~17~~1, wherein the thickness of said inner wall is less than, or equal to, about 0.125 inch.

Claim 18 (currently amended): The ~~filter cartridge housing~~ assembly of claim 12, wherein said first filter media section traverses said first annular flow director, said plurality of filter media sections includes a second filter media section, said second filter media section has a different filter media composition than said first filter media section, said second filter media section has a length in a direction from said first end to said second end that includes at least portions of said second length and said third length of said inner wall sections, and said second media section traverses said second annular flow director.

Claim 19 (original): A system including the assembly of claim 13, in combination with a

U.S. Patent Application No. 09/995,888
Amendment dated May 3, 2004
Reply to Office Action dated February 2, 2004

fluid circulating device, wherein said device has an outlet and an inlet, said entrance port is in fluid communication with said outlet, and said exit port is in fluid communication with said inlet.

Claim 20 (original): A method of filtering a fluid, comprising circulating said fluid through the system of claim 19.

Claim 21 (original): A method of preparing the assembly of claim 13, comprising:
providing said tubular housing;
sealing one of said first and second end connectors to said tubular housing;
introducing a first of said filter media sections into said tubular housing;
settling said first media section in said tubular housing; and
sealing the other of said first and second connectors to said tubular body.

Claim 22 (original): A filter cartridge assembly comprising:

a filter cartridge housing including a tubular housing having a cylindrical shape of constant inner diameter and including a straight inner wall, an outer wall, a first end, and a second end, said inner wall including at least a first section, a second section, and a third section, said first section having a first length in a direction from said first end to said second end, said second section having a second length in a direction from said first end to said second end, said third section having a third length in a direction from said first end to said second end;

a first annular flow director extending radially inwardly from the inner wall of said tubular housing at the intersection of said first section and said second section, and a second annular flow director extending radially inwardly from the inner wall at the intersection of said second section and said third section; and

a plurality of filter media sections, including a first filter media section, within the tubular housing and radially contained by said inner wall, each of said plurality of filter media sections

U.S. Patent Application No. 09/995,888
Amendment dated May 3, 2004
Reply to Office Action dated February 2, 2004

having a different filter media composition, wherein said first filter media section has a length in a direction from said first end to said second end that includes at least portions of at least two of said lengths of the inner wall sections such that said first media section traverses at least one of said first and second annular flow director.

Claim 23 (original): The filter cartridge assembly of claim 22, wherein said assembly further comprises:

a first connector that seals the first end of said tubular housing except at a centrally-located entrance port in said connector where fluid is capable of entering the assembly; and

a second connector that seals the second end of said tubular body except at a centrally-located exit port where fluid is capable of exiting the cartridge.

Claim 24 (original): The filter cartridge assembly of claim 23, wherein said assembly further contains a dialysate fluid.

Claim 25 (original): The filter cartridge assembly of claim 22, wherein said tubular housing comprises a plastic material.

Claim 26 (original): The filter cartridge assembly of claim 25, wherein said plastic material comprises a polypropylene material.

Claim 27 (original): The filter cartridge assembly of claim 22, wherein the thickness of said inner wall is less than, or equal to, about 0.125 inch.

Claim 28 (original): The filter cartridge assembly of claim 22, wherein said first filter media section traverses said first annular flow director, said plurality of filter media sections includes a second filter media section, said second filter media section has a different filter media composition than said first filter media section, said second filter media section has a length in a direction from said first end to said second end that includes at least portions of said second length

U.S. Patent Application No. 09/995,888
Amendment dated May 3, 2004
Reply to Office Action dated February 2, 2004

and said third length of said inner wall sections, and said second media section traverses said second annular flow director.

Claim 29 (original): A system including the filter cartridge assembly of claim 23, in combination with a fluid circulating device, wherein said device has an outlet and an inlet, said entrance port is in fluid communication with said outlet, and said exit port is in fluid communication with said inlet.

Claim 30 (original): A method of preparing the assembly of claim 23, comprising:
providing said tubular housing;
sealing one of said first and second end connectors to said tubular housing;
introducing a first of said filter media sections into said tubular housing;
settling said first media section in said tubular housing; and
sealing the other of said first and second connectors to said tubular body.